

DIMENSIONS & SPECIFICATIONS

H x W x D (10" Standard Legs)..... 33.5"x30.5"x25"
 EPA Certified..... Yes
 Flue Exit..... Top or Back
 Flue Size..... 6"
 Flue Height to Center (Standard Legs)..... 27.75"
 Flue Height to Center (Short Legs)..... 22.75"
 Weight..... 700 lbs.
 Loading Door..... Right or Left
 Loading Door Size (HxW)..... 11"x9"
 Draft Control..... Manual
 Wood Length (Maximum)..... 22"
 Firebox Size..... 2.8 Cubic ft.
 Burn Time..... 8-16 hrs.
 Heat Output Range..... 12,500-80,000 BTU/hr
 Area Heated..... 1,600-2,200 sq. ft.

HxWxD (5" Short Legs)..... 28.5"x30.5"x25"
 Listed to UL 1482..... Yes
 EPA Emissions Rating..... 1.33 grams/hr
 EPA Efficiency..... 81%
 Catalytic Combustor & Secondary Air Standard
 Bottom Heat Shield..... Standard
 Ash Pan..... Optional
 Back Clearance (no protection)..... 36"
 Back Clearance (w/Heat Shield Kit)..... 7"
 Side Clearance..... 24"

