

## Part# FVKSKIT:Load Door Gasket Replacement Keystone Model 204 & Fireview Model 205

**Parts Needed:**

- (4') 3/8 (.375) LD Graphite Gasket
- (1) Bottle of Gasket Glue

**Tools Needed:**

- Scissors
- Putty Knife or Flat Blade Screwdriver
- Wire Brush



*\*Pictures show the Fireview door. The same procedure is used for the Keystone Model.*

1. Make sure the stove is cool. You will need 4' of .375" LD graphite gasket and gasket glue.
2. Open the loading door. Pull straight up on the door. The hinge pins should slide up and out of the hinges in the doorframe. It may be helpful to swing the door back and forth as you lift.
3. Lay the door face down on a suitable work surface. Use a putty knife or flat-head screwdriver to remove the old gasket. A wire brush can be used to clean out glue and old gasket residue from the gasket channel. Vacuum any leftover debris from the door and gasket channel.



4. Apply a 3/16" bead of glue around the prepared channel.
5. Start at the bottom center of the door with one end of the gasket and press it into the channel. Push gasket back slightly as you round the corners to ensure full coverage. Use a putty knife to tuck the gasket in place if necessary. Do not stretch or compress the gasket as you work it around the door. Use sharp scissors to cut the gasket to the proper length and tuck end in.



6. Return the door to the stove. Align the hinge pins with the hinges on the door frame. As you press down on the pins it may be helpful to swing the door back and forth until the door is all the way down on the hinges. Apply lubricant if needed.



7. Close and open the door firmly several times to seat the gasket. If necessary, adjust the set screw on the door latch for the proper tension. Use a 7/16" wrench to loosen the lock nut and a 1/8" Allen wrench to turn the set screw.
8. Allow heat safe gasket glue to dry for 30 minutes.

**If you have questions about the loading door gasket installation, please contact Woodstock Soapstone Co. 9:00-5:00 Monday-Friday or 9:00-12:00 on Saturday. We can be reached at 1-800-866-4344 or by e-mail at [info@woodstove.com](mailto:info@woodstove.com).**